

AQ-110PLV SS:2a

ON SW2 OFF

T1/T2 latch: On / Off

Pulse blocking: On / Off

Blocking function

S5: Fiber loop / AQD

FAST / CBFP

CBFP: 100 ms / 150 ms

I>: 1 A / 5 A

N/A

8

7

6

5

4

3

2

1

ON SW1 OFF

S1: L> / L> + I>

S2: L> / L> + I>

L> / L> + I>

a / b

Scheme selection

8

7

6

5

4

3

2

1

SS:2a		OUTPUTS			
INPUTS	S1	T1	T2	BO1	AQD
	S1	x ¹	x ¹	CBFP ¹	
	S2	x ¹	x ¹	x	x ¹
	S3, S4, S5	x ¹	CBFP ¹	x	x ¹
	Lext> AQ-110PLV (BI1)	x ¹	CBFP ¹		x ¹
	Lext> AQ-101LV (BI2)	x ¹	CBFP ¹	x	x ¹

1) Activates only if channel has been set to light only mode or phase overcurrent signal (I>) is ON.

AQ-101LV SS:0

ON SW1 OFF

L> / L> + I>

S1: L> / L> + I>

Latch: On / Off

Block

Scheme selection

8

7

6

5

4

3

2

1

SS:0		OUTPUTS				
INPUTS	S1 - S5	T1	T2	T3	T4	BO1
		x ¹	x ¹	x ¹	x ¹	x

1) Activates only if channel has been set to light only mode or overcurrent signal (BI2) is ON.

